

NEW! New Holland 20 and 26 hp T1000 Series Boomer™ Sub-Compact Tractors

T1010 T1030



NEW T1000 Series Boomer™ sub-compact tractors cruise through chores with bigger power, unmatched comfort and best-in-class serviceability—all in a convenient size that helps YOU be more productive.

More power and productivity

At 26 horsepower, the T1030 has the most engine horsepower of any sub-compact tractor on the market. Powerful, three-cylinder diesel engines deliver proven strength and reliable service.

The flexibility of two PTOs

Both models are equipped with two power take-offs (PTOs) as standard equipment. The 2200-rpm mid PTO can power a 60-inch mid-mount mower or optional front-attach implements. A rear 540-rpm PTO and 700-pound three-point lift capacity allow you to use any Category I implement.

Superior serviceability

There's no need to raise the hood or remove a front-end loader to add fuel or check the engine oil. The hood lifts on a gas strut and all routine service points are located on the right side of the engine.

A more roomy, comfortable platform

Climb aboard and you have an open roomy platform, high-back comfortable seat and embossed, color-coded controls at your fingertips. The two-range hydrostatic transmission uses two separate direction pedals for easy operation. The sloped hood provides excellent visibility.

More T1000 advantages

- Sensitrak™ option automatically engages front-wheel drive (FWD) for the ultimate in turf-friendly control.
- A foldable ROPS allows you to work under low overhangs when necessary.

Cruise effortlessly through the chores on *your* to-do list with the power and versatility of a T1000 Boomer tractor.

New Holland T1000 Series Boomer™ Sub-Compact Tractor Specifications

Model	T1010	T1030
Engine		
Gross engine hp (kW)	20 (14.9)	26 (19.4)
PTO hp (kW)	15.5 (11.6)	19.7 (14.7)
Rated speed, rpm	3000	3000
Cylinders	3	3
Displacement, cu. in. (L)	58.2 (.95)	69.0 (1.1)
Fuel capacity, gal. (L)	7.1 (26.9)	7.1 (26.9)
Transmissions		
Hydrostatic transmission	2-speed	2-speed
Min/Max forward speed with R4 tires, mph (k/hr)	0-10.3 (16.6)	0-10.3 (16.6)
Brakes		
LocationSingle LH side.....	
TypeWet disc.....	
Power Take Off (PTO)		
Rear	540	540
Mid	2200	2200
Hydraulics		
Pump type	Gear	Gear
System TypeOpen center.....	
Pump capacity, gpm (lpm)*	5.6 (21.2)	5.6 (21.2)
Implement flow, gpm (lpm)	3.75 (14.20)	3.75 (14.21)
Steering priority flow, gpm (lpm)	1.85 (7.0)	1.85 (7.0)
3-point hitch lift capacity, 24 in. behind the lift balls, lb. (kg)	700 (318)	700 (318)
3 Point Hitch ControlSelf centering valve.....	
*@ rated speed		
Axle options		
FWD	Standard	Standard
Sensitrac™ Auto FWD	NA	Optional
Dimensions (with R4 tires)		
Overall length with 3-point hitch, in. (mm)	96.3 (2445)	96.3 (2445)
Overall width (minimum), in. (mm)	46.4 (1180)	46.4 (1180)
Wheelbase, in. (mm)	55.1 (1400)	55.1 (1400)
Height to top of ROPS, in. (mm)	72.4 (1840)	72.4 (1840)
Ground clearance	7.3 (185)	7.3 (185)
Shipping weight w/R4 tires, lbs. (kg)	1455 (660)	1455 (660)
Tire Options		
Turf Tires		
Front18x8.5-8, 4 PR (R3) Turf.....	
Rear26x12-12, 4 PR (R3) Turf.....	
Industrial Tires		
Front18x8.5-8, 4 Pr (R4) Ind.....	
Rear26x12-12, 4PR (R4) Ind.....	

Standard Equipment:

- Toolbox
- Cup holder
- Foldable ROPS
- 12 Volt Accessory power outlet

Optional Equipment:

Front Attachments

- Loader
- Quick-Attach Snow Blower
- Quick-Attach Rotary Broom
- Quick-Attach Front Blade

Mid-Mount Attachments

- 60" Mid-Mount Mower
- Grass Catcher

Rear Attachments

- Finishing Mowers
- Rotary Tiller
- Ballast Box



YOUR NEW HOLLAND DEALER



Visit our Web site at www.newholland.com/na Or, call toll-free: 1-888-290-7377

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.